

Dragonflex: Flame Retardant Compounds

EPDM	T 9608	T 9609	T 9613	T 9616	T 9617	T 9619
Colour	black	black	black	black	natural	black
Hardness Shore A	60	60	60	70	70	60
Density g/cm ³	1.42	1.30	1.35	1.46	1.48	1.34
EN 45545-2	2 mm & 6 mm R 22 HL3 R 23 HL3 R 24 HL3	2 mm & 6 mm R 22 HL2 R 23 HL3 R 24 HL3 3mm R9 HL3	6 mm R 22 HL3 R 23 HL3 R 24 HL3	4 mm R 1 HL2 R 7 HL2 2 mm & 6mm R 22 HL3 R 23 HL3 R 24 HL3	2 mm & 6mm R 22 HL3 R 23 HL3 R 24 HL3	6mm R 22 HL2 R 23 HL2 R 24 HL2
EN 13501-1				Bfl-S1 B-s1, d0		
NF EN 60695-11-10/ UL94-V:2013	V-0 @3mm		V-0 @3mm	V-0 @3mm	V-0 @3mm	
DIN 4102				B2		



Dragonflex: Flame Retardant Compounds

NR	A 3150	A 3155	A 3160	A 3180	A 9670
Colour	black	black	black	black	natural
Hardness Shore A	50	55	60	80	70
Density g/cm ³	1.39	1.44	1.51	1.48	1.45
EN 45545-2	4 mm R 9 HL2	4 mm R 9 HL1	4 mm R 9 HL2	4 mm R 9 HL2	3 mm R 9 HL2
EN 13501-1					
NF EN 60695-11-10/ UL94-V:2013			V-0 @3mm		

