

Dragonflex: Flame Retardant Compounds

EPDM	T 9608	T 9609	T 9612 (T9609- MB25)	T 9613	T 9616	T 9617	T 9619	T 9619	T 9622
Colour	black	black	black	black	black	natural	black	black	black
Hardness: Shore A	60	60	60	60	70	70	60	60	70
Density g/cm ³	1.42	1.30	1.46	1.35	1.46	1.48	1.34	1.34	1.5
EN 45545-2	2 mm & 6 mm R 22: HL3 R 23: HL3 R 24: HL3	2 mm & 6 mm R 22: HL2 R 23: HL3 R 24: HL3 3mm R9: HL3		6 mm R 22: HL3 R 23: HL3 R 24: HL3	4 mm R 1: HL2 R 7: HL2 2 mm & 6mm R 22: HL3 R 23: HL3 R 24: HL3	2 mm & 6mm R 22: HL3 R 23: HL3 R 24: HL3	6mm R 22: HL2 R 23: HL2 R 24: HL2	6mm R 22: HL2 R 23: HL2 R 24: HL2	3mm R 22: HL3 R 23: HL3 R 24: HL3
EN 13501-1					Bfl-S1 (4mm) B-s1, d0 (6mm)				
NF EN 60695-11-10/ UL94-V:2013	V-0 @3mm	not classified V0-V1-V2	V0 @3mm V0 @6mm	V-0 @3mm	V-0 @3mm	V-0 @3mm			
DIN 4102					B2 (4mm)				
NFPA 130: 2023	Qualified (5mm)								



Barzloostrasse 1
8330 Pfäffikon/ZH

Dragonflex: Flame Retardant Compounds

NR	A 3150	A 3155	A 3160	A 3170	A 3180	A 9670
Colour	black	black	black	black	black	natural
Hardness Shore A	50	55	60	70	80	70
Density g/cm ³	1.39	1.44	1.51	1.46	1.48	1.45
EN 45545-2	4 mm R 9 HL2	4 mm R 9 HL1	4 mm R 9 HL2	4 mm R 9 HL2	4 mm R 9 HL2	3 mm R 9 HL2
EN 13501-1						
NF EN 60695-11-10/ UL94-V:2013			V-0 @3mm			

