

ACTUAL AQUAFLEX® SUNAFLEX®- DRINKING WATER COMPOUNDS

T = EPDM	BfR	EN 681-1	D - Elastomer guidelines UBA	D - DVGW standard W-270	GB - WRAS *, cold water	GB - WRAS *, hot water	F - ACS **	A - ÖNORM B5014/1	Elastomer	Hardness (Shore A)	Colour
T 8715	x	-	23°C	✓	✓	-	✓	-	EPDM	50	● black
T 8184		conform	23°C	✓	-	-	-	-	EPDM	60	● black
T 8165	x	DVGW WA/WC	23°C	✓	✓	✓	✓	✓	EPDM	70	● black
T 8289	x	conform	23°C	✓	✓	-	✓	-	EPDM	70	● black
T 8193	x	DVGW WA/WC	60°C	✓	✓	-	✓	✓	EPDM	80	● black
T 9635	x	conform	85°C	✓	✓	✓	✓	✓	EPDM	70	● black
T 9643		conform	85°C	✓	-	-	-	-	EPDM	80	● black
T 8157	x	DVGW WA/WC	60°C	✓	✓	✓	✓	-	EPDM	60	● black
T 5817	x	planned	60°C	D2	planned	planned	planned		EPDM	70	● black
T 5818	x	planned	60°C	D1	planned	planned	planned		EPDM	70	● black
T 5862	x		85°C	in testing					EPDM	70	● black
T 9696	x		planned	planned					EPDM	70	● black
T 9644	x		planned	planned					EPDM	80	● black